



Yamamoto

 Yamamoto North America



WUN150

Yamamoto North America LLC
PO Box 3264,
205 S. Lee St.
Bloomington, IL 61701



866-204-0519
8am-5pm Mon-Fri Central Time
Yamamoto-NA.com

Model No.	WUN150		
Capacity (Best Practices)	70kg	150lbs	
Drum	Diameter	φ1140mm	Φ44.9"
	Depth	620mm	24.4"
	L / Cubic Feet	632L	22.3cu.ft
Machine Size	Height	1900mm(2200mm)	74.8"(86.6")
	Width	1646mm(1850mm)	64.8"(72.8")
	Depth	1752mm(1990mm)	69.0"(78.4")
Weight of empty machine	2100kg	4630lbs	
Crated Weight	2150kg	4740lbs	
Drum Speed	Washing Speed	20~40rpm	
	Extraction Speed	240~720rpm	
G - Force	High Speed	330G	
Dynamic Loading	Frequency	12Hz	
	Dynamic floor weight	1600kg/m ²	327.7lb/ft ²
Loading Door	Door Height	990mm	39"
	Door Opening	φ610mm	φ24"
Power	Electrical phase, Voltage, Frequency	3-phase, AC208V~230V, 60Hz	
	Maximum Amperage	50A	
Minimum Supply-Circuit Conductor Ampacity	60A		
Maximum Rating of Supply Circuit Overcurrent Protective Device	60A		
Motor Size	20HP (15KW)		
Cold water Supply	Connection Port	2NPT	
	Water Supply Pressure	0.1-0.3MPa , 14.5-43.5psi , 1-3bar	
Hot water Supply	Connection Port	2NPT	
	Water Supply Pressure	0.1-0.3MPa , 14.5-43.5psi , 1-3bar	
Detergent Cup Water	Connection Port	3/4NPT	
	Water Supply Pressure	0.1-0.3MPa , 14.5-43.5psi , 1-3bar	
Steam Supply	Connection Port	1NPT	
	Drain Port	3/8NPT	
	Pressure	0.4-0.6MPa , 58-87psi , 4-6bar	
Water Drain	Connection Port	4NPT	
Compressed-Air	Connection Port	3/8" O.D.	
	Pressure	0.7-1.0MPa , 101.5-145psi , 7-10bar	
	Setting Pressure of Regulator	0.6MPa , 87.1psi , 6bar	
Usage environment	Temperature Of Surrounding	5-45°C	41-113°F
	Humidity	30-85%	

